108 Conductive Epoxy Terrazzo Epoxy Ctg

Part A

Printed: 04/14/2020 Revision: 04/14/2020

Page: 1

Supersedes Revision: 05/28/2015

+1 (513)943-4225

1. Product and Company Identification

Product Code: 108-COND-012

Product Name: 108 Conductive Epoxy Terrazzo Epoxy Ctg Part A

Key Resin Company **Company Name: Phone Number:**

> 4050 Clough Woods Dr. Batavia, OH 45103

Chemtrec (USA) **Emergency Contact:** (800)424-9300

> Chemtrec (International) +1 (703)527-3887

Intended Use: Industrial floor coatings.

2. Hazards Identification

Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2A

Skin Sensitization, Category 1B

Aquatic Toxicity (Acute), Category 2

Aquatic Toxicity (Chronic), Category 2

Carcinogenicity, Category 2

Specific Target Organ Toxicity (single exposure), Category 3







Warning

Warning

GHS Hazard Phrases: H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H317 - May cause an allergic skin reaction.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects. H351 - Suspected of causing cancer (respiratory).

H335 - May cause respiratory irritation.

GHS Precaution Phrases: P281 - Use personal protective equipment as required.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P362+364 - Take off contaminated clothing and wash it before reuse.

P273 - Avoid release to the environment.

P271 - Use only outdoors or in a well-ventilated area.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water. P332+313 - If skin

> irritation occurs, get medical advice/attention. P362 - Take off contaminated clothing. P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation

persists, get medical advice/attention.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P342+311 - If experiencing respiratory symptoms call a POISON CENTER or

doctor/physician.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P310 -

Immediately call a POISON CENTER or doctor/physician.

P391 - Collect spillage.

GHS Storage and Disposal

Phrases:

P402+404 - Store in a dry place and/or in closed container. P501 - Dispose of

contents/container to local, state, and federal authority requirements.

Printed: 04/14/2020 108 Conductive Epoxy Terrazzo Epoxy Ctg Revision: 04/14/2020 Part A Supersedes Revision: 05/28/2015

This material is classified as hazardous under OSHA regulations. OSHA Regulatory Status:

May cause eye irritation. May cause skin irritation. May cause skin sensitization, an **Potential Health Effects**

allergic reaction, which becomes evident on reexposure to this material. (Acute and Chronic):

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation. **Eve Contact:** Causes eye irritation.

Ingestion: May be harmful if swallowed.

Medical Conditions Generally Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

Aggravated By Exposure:

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	50 - 70 %
28553-12-0	1,2-Benzenedicarboxylic acid, Diisononyl ester	5.0 - 15 %
67762-38-3	Fatty acids, C16-18 and C18-unsatd., Me esters	5.0 - 15 %
1333-86-4	Carbon black	1.0 - 10 %
107-41-5	2,4-Pentanediol, 2-Methyl-	1.0 - 5.0 %
1330-20-7	Xylene	<1.4 %

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention

immediately.

In Case of Skin Contact: In case of contact, immediately wash skin with soap and copious amounts of water.

Remove contaminated clothing and shoes. Get medical attention if irritation develops or

persists.

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. In Case of Eye Contact:

Assure adequate flushing by separating the eyelids with fingers. Call a physician.

If swallowed, wash out mouth with water provided person is conscious. Call a physician In Case of Ingestion:

immediately. Do not induce vomiting. For further assistance, contact your local Poison

Control Center.

Signs and Symptoms Of

Exposure:

May cause skin, eye, and respiratory irritation. May cause allergic skin reaction.

5. Fire Fighting Measures

> 200.00 C (392.0 F) Method Used: Pensky-Marten Closed Cup Flash Pt:

LEL: NE UEL: NE **Explosive Limits:**

Autoignition Pt: No data.

Suitable Extinguishing Media: Dry chemical, CO2, water spray or regular foam.

Do not use a direct water stream, which may spread fire. Unsuitable Extinguishing

Media:

As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and

Fire Fighting Instructions:

Hazards:

Product is not considered a fire hazard. Closed containers may rupture (due to build up

in pressure) when exposed to extreme heat.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format

Page: 2

108 Conductive Epoxy Terrazzo Epoxy Ctg

Part A

Revision: 04/14/2020 Supersedes Revision: 05/28/2015

Printed: 04/14/2020

Page: 3

6. Accidental Release Measures

Protective Precautions, Protective Equipment and Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Emergency Procedures: Environmental Precautions:

Prevent entry into waterways, sewers, basements or confined areas. PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Steps To Be Taken In Case Material Is Released Or

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the

area.

7. Handling and Storage

Precautions To Be Taken in

Provide adequate ventilation. Do not breathe vapor. Do not get in eyes, on skin or on

Handling:

clothing.

Precautions To Be Taken in

Keep container tightly closed in a dry and well-ventilated place.

Storing:

Spilled:

Wash thoroughly after handling. Other Precautions:

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
28553-12-0	1,2-Benzenedicarboxylic acid, Diisononyl ester	No data.	No data.	No data.
67762-38-3	Fatty acids, C16-18 and C18-unsatd., Me esters	No data.	No data.	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3.5 mg/m3	No data.
107-41-5	2,4-Pentanediol, 2-Methyl-	No data.	TLV: 25 ppm CEIL: 121 mg/m3	No data.
1330-20-7	Xylene	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.

Respiratory Equipment (Specify Type):

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection: Safety glasses, or goggles.

Protective Gloves: Nitrile rubber and Neoprene are recommended.

Other Protective Clothing: Where splashing is possible, full chemically resistant protective clothing, safety glasses

or face shield and boots are required.

Engineering Controls (Ventilation etc.):

Good general ventilation should be sufficient to control airborne levels. Safety shower

and eye bath.

Work/Hygienic/Maintenance

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash

Practices:

thoroughly after handling.

Environmental Exposure

Controls:

Avoid runoff into storm sewers and ditches which lead to waterways. May be hazardous

to the environment if released in large quantities.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format

108 Conductive Epoxy Terrazzo Epoxy Ctg

Part A

Printed: 04/14/2020 Revision: 04/14/2020 Supersedes Revision: 05/28/2015

Page: 4

9. Physical and Chemical Properties [X] Liquid [] Solid Physical States: [] Gas Appearance and Odor: Epoxy odor. Appearance: Dark. Liquid. Melting Point: NE **Boiling Point:** NE **Decomposition Temperature: NE** Autoignition Pt: No data. Flash Pt: > 200.00 C (392.0 F) Method Used: Pensky-Marten Closed Cup UEL: NE **Explosive Limits:** LEL: NE Specific Gravity (Water = 1): ~ 1.11 ~ 9.24 LB/GL Density: Vapor Pressure (vs. Air or mm Hg): Vapor Density (vs. Air = 1): NE **Evaporation Rate:** NE Solubility in Water: No data. **Solubility Notes:** Practically insoluble. NE Saturated Vapor **Concentration:** < 1.5 % by weight. Percent Volatile: VOC / Volume: NP 10. Stability and Reactivity Avoid: acids, alkalis, oxidizing agents. Reactivity: Stability: Unstable [] Stable [X]

Avoid uncontrolled contact with amines. Extreme temperatures. Conditions To Avoid -

Instability:

Incompatibility - Materials To Avoid strong acids, bases, and oxidizing agents.

Avoid:

Hazardous Decomposition Or Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide.

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Polymerization:

Conditions To Avoid -Will not undergo hazardous polymerization in normal storage conditions.

Hazardous Reactions:

Part

108 Conductive Epoxy Terrazzo Epoxy Ctg

Printed: 04/14/2020 Revision: 04/14/2020 Supersedes Revision: 05/28/2015

Page: 5

Part A

11. Toxicological Information

Toxicological Information: May cause sensitization by skin contact.

CAS# 1330-20-7: Acute toxicity, LD50, Oral, Rat, 4300. MG/KG. Results: Liver: Other changes. Kidney, Ureter, Bladder:Other changes.; AMA Archives of Industrial Health.,

For publisher information, see AEHLAU, Chicago, IL, Vol/p/yr: 14,387, 1956

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H. Results: Behavioral: Convulsions

or effect on seizure threshold. Behavioral: Ataxia. Lungs, Thorax, or

Respiration:Dyspnea.; Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial

Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Irritation or Corrosion:

Skin Irritation. Irritating to eyes. May cause skin, eye, and respiratory irritation.

Symptoms related to

May cause redness, rash on skin.

Toxicological

Characteristics:

Chronic Toxicological

Skin sensitization.

Effects:

12. Ecological Information

General Ecological

Avoid release to the environment. May be hazardous to the environment if released in

Information:

large quantities.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

Not readily biodegradable.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: not reported, unknown.

13. Disposal Considerations

Waste Disposal Method:

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: (Non-Bulk)

Not Regulated.

(Bulk)

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin) MARINE

POLLUTANT.

NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.

DOT Hazard Class: 9 CLASS 9

UN/NA Number: UN3082 Packing Group: III

Precautionary Label: Avoid skin and eye contact. May cause eye and skin irritation. May cause skin

sensitization. Wear protective equipment and clothing. Always read MSDS/SDS

before use.

108 Conductive Epoxy Terrazzo Epoxy Ctg

Part A

Printed: 04/14/2020 Revision: 04/14/2020 Supersedes Revision: 05/28/2015

Page: 6

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin) MARINE

POLLUTANT.

Note: The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. Shipment compliance is the responsibility of the person offering

the product for transport.

UN Number: 3082 Packing Group: III

Hazard Class: 9 - CLASS 9

IMDG MFAG Number: FA-SF

IMDG EMS Page: Yes

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: (Non-Bulk)

Not Regulated.

(Bulk)

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin) MARINE

POLLUTANT.

NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
28553-12-0	1,2-Benzenedicarboxylic acid, Diisononyl ester	No	No	No
67762-38-3	Fatty acids, C16-18 and C18-unsatd., Me esters	No	No	No
1333-86-4	Carbon black	No	No	No
107-41-5	2,4-Pentanediol, 2-Methyl-	No	No	No
1330-20-7	Xylene	No	Yes 100 LB	Yes

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard **'Hazard Categories' defined** [X] Yes [] No Chronic (delayed) Health Hazard

for SARA Title III Sections [] Yes [X] No Fire Hazard

311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard

[] Yes [X] No Reactive Hazard

SAFETY DATA SHEET 108 Conductive Epoxy Terrazzo Epoxy Ctg

Part A

Revision: 04/14/2020 Supersedes Revision: 05/28/2015

Printed: 04/14/2020

Page: 7

Regulatory Information: California Prop. 65:

This product contains the following Proposition 65 chemicals: Acetylene Black, Carbon

Black CAS# 1333-86-4.

16. Other Information

04/14/2020 Revision Date:

Hazard Rating System:

HEALTH **FLAMMABILITY PHYSICAL** 0 **PPE** Х

HMIS:

Additional Information About CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED This Product: NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or

Disclaimer:

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however the Key Resin Company makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof.