Printed: 08/14/2019 Revision: 08/14/2019

Page: 1

Supersedes Revision: 11/06/2014

+1 (513)943-4225

1. Product and Company Identification

Product Code: 108-FCB

Product Name: 108 Fast Cure Hardener - Part B
Trade Name: 108 Fast Cure Hardener - Part B

Company Name: Key Resin Company Phone Number:

4050 Clough Woods Dr. Batavia, OH 45103

Emergency Contact: Chemtrec (USA) (800)424-9300

Chemtrec (International) +1 (703)527-3887

#### 2. Hazards Identification

Skin Corrosion/Irritation, Category 1B

Skin Sensitization, Category 1

Serious Eye Damage/Eye Irritation, Category 1

Acute Toxicity: Oral, Category 4
Acute Toxicity: Inhalation, Category 4
Acute Toxicity: Skin, Category 4
Toxic To Reproduction, Category 2







**Danger** 

Warning

Warning

GHS Hazard Phrases: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H302 - Harmful if swallowed. H332 - Harmful if inhaled.

H312 - Harmful in contact with skin.

H361 - Suspected of damaging fertility or the unborn child .

**GHS Precaution Phrases:** P262 - Do not get in eyes, on skin, or on clothing.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P271 - Use only outdoors or in a well-ventilated area.

P202 - Do not handle until all safety precautions have been read and understood.

GHS Response Phrases: P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower. P333+313 - If skin irritation or rash occurs, seek

medical advice/attention. P363 - Wash contaminated clothing before reuse.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P313 - Get medical

advice/attention.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P315 - Get

immediate medical advice/attention.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P314 - Get medical attention/advice if you feel unwell.

**GHS Storage and Disposal** 

P405 - Store locked up.

Phrases:

P501 - Dispose of contents/container to local, state, and federal authority requirements.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Page: 2 Printed: 08/14/2019 Revision: 08/14/2019

Supersedes Revision: 11/06/2014

**Potential Health Effects** Corrosive to eyes and skin. Causes burns. May be harmful if swallowed. Irritating to

(Acute and Chronic): respiratory system. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on

skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Aspiration hazard if

swallowed. Can enter lungs and cause damage.

**Inhalation:** Corrosive to respiratory tract. May cause respiratory sensitization.

**Skin Contact:** Contact with substance may cause severe burns to skin. Symptoms may include

redness, edema, drying, defatting and cracking of the skin.

**Eye Contact:** Corrosive/irritation to eyes. Causes eye burns.

**Ingestion:** Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal

tract if it is swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway,

esophagus and possibly the digestive tract.

Medical Conditions Generally Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

Aggravated By Exposure:

# 3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
111-40-0	Diethylenetriamine	30 - 45 %
100-51-6	Benzenemethanol	30 - 45 %
80-05-7	4,4'-Isopropylidenediphenol	15 - 25 %

#### 4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention

immediately.

In Case of Skin Contact: In case of contact, immediately wash skin with soap and copious amounts of water.

Remove contaminated clothing and shoes. Get medical attention if irritation develops or

persists.

In Case of Eye Contact: In case of contact with eyes, flush with copious amounts of water for at least 15 minutes.

Assure adequate flushing by separating the eyelids with fingers. Get medical attention

immediately.

In Case of Ingestion: If swallowed, wash out mouth with water provided person is conscious. Do not induce

vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or

having convulsions. Get medical attention immediately.

Signs and Symptoms Of

Exposure:

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production,

with marked redness and swelling of the conjunctiva.

Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying,

defatting and cracking of the skin.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and

cough.

Printed: 08/14/2019 Revision: 08/14/2019

Page: 3

Supersedes Revision: 11/06/2014

5. Fire Fighting Measures

Flash Pt: > 200.00 F (93.3 C) Method Used: Pensky-Marten Closed Cup

LEL: NE UEL: NE **Explosive Limits:** 

**Autoignition Pt:** No data.

Suitable Extinguishing Media: CO2, dry chemical, dry sand, alcohol-resistant foam. Unsuitable Extinguishing Do not use a direct water stream, which may spread fire.

Media:

Fire Fighting Instructions: Protective Equipment: Wear self-contained breathing apparatus and protective clothing

to prevent contact with skin and eyes.

Flammable Properties and

Hazards:

Combustible material: may burn but does not ignite readily.

#### 6. Accidental Release Measures

**Protective Precautions, Protective Equipment and Emergency Procedures:** 

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

**Environmental Precautions:** Prevent entry into waterways, sewers, basements or confined areas. PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL. Steps To Be Taken In Case

Material Is Released Or

Spilled:

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the

area.

# 7. Handling and Storage

Handling:

Precautions To Be Taken in Provide adequate ventilation. Wear all personal protection required in section 8.

Precautions To Be Taken in Keep container tightly closed in a dry and well-ventilated place. Store away from

Storing:

incompatible material.

Other Precautions: Wash thoroughly after handling.

# 8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
111-40-0	Diethylenetriamine	No data.	TLV: 1 ppm	No data.
100-51-6	Benzenemethanol	No data.	No data.	No data.
80-05-7	4,4'-Isopropylidenediphenol	No data.	No data.	No data.

Respiratory Equipment (Specify Type):

However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Normally when good engineering controls are used, no respiratory protection is needed.

**Eye Protection:** Safety glasses, or goggles.

**Protective Gloves:** Nitrile rubber and Neoprene are recommended.

Where splashing is possible, full chemically resistant protective clothing, safety glasses Other Protective Clothing:

or face shield and boots are required.

**Engineering Controls** (Ventilation etc.):

Good general ventilation should be sufficient to control airborne levels. Safety shower

and eye bath.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc. **GHS** format

Printed: 08/14/2019 Revision: 08/14/2019

Page: 4

Supersedes Revision: 11/06/2014

Work/Hygienic/Maintenance

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash

Practices:

thoroughly after handling.

**Environmental Exposure** 

Avoid runoff into storm sewers and ditches which lead to waterways.

Controls:

9. Physical and Chemical Properties

[X] Liquid [ ] Solid [ ] Gas Physical States:

Odor: amine-like. Appearance and Odor:

Appearance: Liquid. amber.

NE Melting Point: **Boiling Point:** ΝE **Decomposition Temperature: NE** 

Autoignition Pt: No data.

Flash Pt: > 200.00 F (93.3 C) Method Used: Pensky-Marten Closed Cup

**Explosive Limits:** LEL: NE UEL: NE

**Specific Gravity (Water = 1):** ~ 1.019 - 1.043 ~ 8.5 - 8.7 LB/GL Density:

Vapor Pressure (vs. Air or

NE

mm Hg):

NE Vapor Density (vs. Air = 1): NE **Evaporation Rate:** Insoluble Solubility in Water:

Saturated Vapor

Concentration:

NE

Percent Volatile: N.A. NΡ VOC / Volume:

10. Stability and Reactivity

Avoid: acids, alkalis, oxidizing agents. Reactivity:

Stability: Unstable [ ] Stable [ X ]

**Conditions To Avoid -**

Extreme temperatures.

Instability:

**Incompatibility - Materials To** Avoid strong acids, bases, and oxidizing agents.

Avoid:

Hazardous Decomposition Or Nitrogen oxides, Phenolics. Carbon monoxide, Carbon dioxide, Ammonia. Amines.

Byproducts:

Possibility of Hazardous Will occur [ ] Will not occur [X]

Polymerization:

Conditions To Avoid -Will not undergo hazardous polymerization in normal storage conditions.

Hazardous Reactions:

Page: 5
Printed: 08/14/2019
Revision: 08/14/2019

Supersedes Revision: 11/06/2014

# 11. Toxicological Information

Toxicological Information: May cause sensitization by skin contact. May cause redness, rash on skin.

Irritation or Corrosion: Corrosive! Damages skin and eyes.

Symptoms related to

Skin: Contact with substance may cause severe burns to skin. Symptoms may include

**Toxicological** redness, edema, drying, defatting and cracking of the skin.

**Characteristics:** Eyes: Symptoms may include discomfort or pain, excess blinking and tear production,

with marked redness and swelling of the conjunctiva. Permanent eye damage including

blindness could result.

Inhalation: Inhalation of vapors/fumes causes respiratory irritation with throat discomfort,

coughing or difficulty breathing.

Chronic Toxicological

Effects:

Skin sensitization.

### 12. Ecological Information

General Ecological Avoid release to the environment. Do not empty into drains. May be hazardous to the

**Information:** environment if released in large quantities.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

Not readily biodegradable.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: not reported, unknown.

### 13. Disposal Considerations

Waste Disposal Method: Incinerate or dispose of unused material, residues and containers in a licensed facility in

accordance with all applicable local, state and federal regulations. Do not discharge

substance/product into sewage system.

# 14. Transport Information

#### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Corrosive Liquid, N.O.S. (Aliphatic Amines) (Diethylenetriamine)

**DOT Hazard Class:** 8 CORROSIVE

UN/NA Number: UN1760 Packing Group: III

Precautionary Label: Corrosive! Damages skin and eyes. Avoid skin and eye contact. May cause eye and

skin irritation. May cause skin sensitization. Wear protective equipment and clothing.

Always read MSDS/SDS before use.



#### MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Corrosive Liquid, N.O.S. (Aliphatic Amines)

UN Number: 1760 Packing Group: III

Hazard Class: 8 - CORROSIVE

IMDG EMS Number: FA,SB IMDG MFAG Number:

IMDG EMS Page: No

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Printed: 08/14/2019 Revision: 08/14/2019

Page: 6

Supersedes Revision: 11/06/2014

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: (Aliphatic Amines) Corrosive Liquid, N.O.S.

# 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
111-40-0	Diethylenetriamine	No	No	No
100-51-6	Benzenemethanol	No	No	No
80-05-7	4,4'-Isopropylidenediphenol	No	No	Yes

**This material meets the EPA** [X] Yes [ ] No Acute (immediate) Health Hazard **'Hazard Categories' defined** [X] Yes [ ] No Chronic (delayed) Health Hazard

for SARA Title III Sections

[ ] Yes [X] No Fire Hazard

**311/312 as indicated:** [ ] Yes [X] No Sudden Release of Pressure Hazard

[ ] Yes [X] No Reactive Hazard

#### 16. Other Information

**Revision Date:** 08/14/2019

**Hazard Rating System:** 

HEALTH 3
FLAMMABILITY 1
PHYSICAL 0
PPE X

HMIS:

Additional Information About CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED

This Product: NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or

Disclaimer:

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however the Key Resin Company makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the

recommendations, and assumes no liabilities to any user thereof.