445 Clear WB Urethane Finishcoat (Satin)

Part A

Printed: 07/06/2021

Revision: 07/06/2021 Supersedes Revision: 01/10/2017

Page: 1

# 1. Product and Company Identification

**Product Code:** 445-CLEAR

Product Name: 445 Clear WB Urethane Finishcoat (Satin) Part A

Key Resin / Flowcrete **Phone Number: Company Name:** 

4050 Clough Woods Dr. +1 (513)943-4225

Batavia, OH 45103

Chemtrec (USA) **Emergency Contact:** (800)424-9300

> Chemtrec (International) +1 (703)527-3887

Industrial floor coatings. Intended Use:

### 2. Hazards Identification

Serious Eye Damage/Eye Irritation, Category 2B

Skin Corrosion/Irritation, Category 3

**GHS Hazard Phrases:** H320 - Causes eye irritation.

> H316 - Causes mild skin irritation. H335 - May cause respiratory irritation. H303 - May be harmful if swallowed.

**GHS Precaution Phrases:** P103 - Read label before use. P281 - Use personal protective equipment as required.

P262 - Do not get in eyes, on skin, or on clothing. P261 - Avoid breathing

mist/vapors/spray.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove **GHS Response Phrases:** 

> contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation persists, get medical advice/attention.

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P332+313 - If skin

irritation occurs, get medical advice/attention.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P314 - Get medical attention/advice if you feel unwell. P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P313 - Get

medical advice/attention.

P404 - Store in a closed container. GHS Storage and Disposal

Phrases: P402 - Store in a dry place.

P401 - Store: at 45-80 degrees Fahrenheit.

This material is classified as hazardous under OSHA regulations. **OSHA Regulatory Status:** 

**Potential Health Effects** 

May cause eye irritation. May cause skin irritation. May cause respiratory irritation.

(Acute and Chronic):

Inhalation: May cause respiratory irritation.

Skin Contact: May cause skin irritation. Eye Contact: May cause eye irritation. May be harmful if swallowed. Ingestion:

Medical Conditions Generally Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

Aggravated By Exposure:

# 3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration	
102-71-6	Triethanolamine	0.97 - 5.6 %	
5131-66-8	2-Propanol, 1-Butoxy-	0.97 - 5.6 %	
2807-30-9	Ethylene glycol monopropyl ether	2.7 %	
872-50-4	N-Methyl-2-pyrrolidone	1.5 %	

445 Clear WB Urethane Finishcoat (Satin)

Part A

Printed: 07/06/2021 Revision: 07/06/2021 Supersedes Revision: 01/10/2017

Page: 2

4. First Aid Measures

Emergency and First Aid

Procedures:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is In Case of Inhalation:

difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention

immediately.

In case of contact, immediately wash skin with soap and copious amounts of water. In Case of Skin Contact:

Remove contaminated clothing and shoes. Get medical attention if irritation develops or

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. In Case of Eye Contact:

Assure adequate flushing by separating the eyelids with fingers. Call a physician.

In Case of Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician

immediately. For further assistance, contact your local Poison Control Center.

Signs and Symptoms Of

Mild irritation effect.

Exposure:

5. Fire Fighting Measures

NA Method Used: Not Applicable Flash Pt: LEL: NE UEL: NE **Explosive Limits:** 

No data. Autoignition Pt:

Suitable Extinguishing Media: Will not support combustion. Unsuitable Extinguishing Will not support combustion.

Media:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing Fire Fighting Instructions:

to prevent contact with skin and eyes. Use water spray to cool unopened containers.

Flammable Properties and

Hazards:

Product will not support combustion as supplied. Product is not considered a fire hazard. Closed containers may rupture (due to build up in pressure) when exposed to extreme

heat.

6. Accidental Release Measures

Protective Precautions, **Protective Equipment and Emergency Procedures:** 

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves.

**Environmental Precautions:** Steps To Be Taken In Case

Prevent entry into waterways, sewers, basements or confined areas. PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Material Is Released Or

Evacuate area. Absorb with sand or vermiculite and place in closed containers for

disposal. Ventilate the area.

7. Handling and Storage

Handling:

**Precautions To Be Taken in** Provide adequate ventilation. Do not breathe vapor. Do not get in eyes, on skin or on

clothing.

Precautions To Be Taken in

Keep from freezing. Keep container closed when not in use.

Storing:

Spilled:

Other Precautions: Wash thoroughly after handling.

8. Exposure Controls/Personal Protection

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Part A

Printed: 07/06/2021 445 Clear WB Urethane Finishcoat (Satin) Revision: 07/06/2021 Supersedes Revision: 01/10/2017

Page: 3

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
102-71-6	Triethanolamine	No data.	TLV: 5 mg/m3	No data.
5131-66-8	2-Propanol, 1-Butoxy-	No data.	No data.	No data.
2807-30-9	Ethylene glycol monopropyl ether	No data.	No data.	No data.
872-50-4	N-Methyl-2-pyrrolidone	No data.	No data.	No data.

**Respiratory Equipment** 

(Specify Type):

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Safety glasses, or goggles. Eye Protection:

Nitrile rubber and Neoprene are recommended. **Protective Gloves:** 

Other Protective Clothing: Where splashing is possible, full chemically resistant protective clothing, safety glasses

or face shield and boots are required.

**Engineering Controls** 

(Ventilation etc.):

Good general ventilation should be sufficient to control airborne levels. Safety shower

and eye bath.

Work/Hygienic/Maintenance

Practices:

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash

thoroughly after handling.

**Environmental Exposure** 

Controls:

Avoid release to the environment. Avoid runoff into storm sewers and ditches which lead

to waterways.

# 9. Physical and Chemical Properties

**Physical States:** [ ] Gas [X] Liquid [ ] Solid

Milky. Faint. Appearance and Odor: **Melting Point:** No data.

**Boiling Point:** 212.00 F (100.0 C)

Autoignition Pt: No data.

Flash Pt: NA Method Used: Not Applicable LEL: NE UEL: NE **Explosive Limits:** 

Specific Gravity (Water = 1): 1.03 Density: ~ 8.6 ΝE

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): NE NE **Evaporation Rate:** Solubility in Water: Soluble Water soluble. **Solubility Notes:** 

NE Saturated Vapor

Concentration:

>= 70.0 % by volume. Percent Volatile:

Part A

445 Clear WB Urethane Finishcoat (Satin)

Printed: 07/06/2021 Revision: 07/06/2021

Page: 4

Supersedes Revision: 01/10/2017

10. Stability and Reactivity

Reactivity: None known.

Stability: Unstable [ ] Stable [X]

**Conditions To Avoid -**None known.

Instability:

Incompatibility - Materials To Strong oxidizing agents.

Avoid:

Hazardous Decomposition Or None known.

Byproducts:

**Possibility of Hazardous** 

Will occur [ ] Will not occur [X]

Polymerization:

**Conditions To Avoid -**None known.

**Hazardous Reactions:** 

11. Toxicological Information

Product not considered to be a toxic mixture. Toxicological Information:

Irritation or Corrosion: No data available. No data available. Symptoms related to

**Toxicological** Characteristics:

**Chronic Toxicological** 

Effects:

No data available.

12. Ecological Information

Do not empty into drains. Avoid release to the environment.

General Ecological

Information:

Results of PBT and vPvB

assessment: Persistence and

No data available.

No data available.

Degradability:

Bioaccumulative Potential: not reported, unknown.

not reported, unknown. Mobility in Soil:

13. Disposal Considerations

Incinerate or dispose of unused material, residues and containers in a licensed facility in Waste Disposal Method:

accordance with all applicable local, state and federal regulations. Do not discharge

substance/product into sewage system.

14. Transport Information

LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Not Regulated.

**DOT Hazard Class: UN/NA Number:** 

May cause skin, eye, and respiratory irritation. Always read Safety Material Data **Precautionary Label:** 

Sheet before use.

445 Clear WB Urethane Finishcoat (Satin)

Page: 5 Printed: 07/06/2021 Revision: 07/06/2021

Supersedes Revision: 01/10/2017

Part A

MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Not Regulated.

AIR TRANSPORT (ICAO/IATA):

Not Regulated. ICAO/IATA Shipping Name:

### 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
102-71-6	Triethanolamine	No	No	No
5131-66-8	2-Propanol, 1-Butoxy-	No	No	No
2807-30-9	Ethylene glycol monopropyl ether	No	No	Yes-Cat. N230
872-50-4	N-Methyl-2-pyrrolidone	No	No	Yes

This material meets the EPA [X] Yes [ ] No Acute (immediate) Health Hazard 'Hazard Categories' defined [ ] Yes [X] No Chronic (delayed) Health Hazard

for SARA Title III Sections [ ] Yes [X] No Fire Hazard

311/312 as indicated:

[ ] Yes [X] No Sudden Release of Pressure Hazard

[ ] Yes [X] No Reactive Hazard

### 16. Other Information

**Revision Date:** 07/06/2021

**Hazard Rating System:** 

HEALTH **FLAMMABILITY** 1 PHYSICAL 0 PPE Х

HMIS:

Additional Information About CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED

This Product: NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or The information contained in this MSDS is taken from sources believed to be accurate as Disclaimer:

of the date hereof; however the Key Resin Company makes no expressed or implied

warranty in respect to the accuracy of the information or the suitability of the

recommendations, and assumes no liabilities to any user thereof.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format