#570 Epoxy/Polysiloxane Part A

Printed: 07/06/2021 Revision: 07/06/2021

Page: 1

Supersedes Revision: 08/03/2015

1. Product and Company Identification

Product Code: 570-A

Product Name: #570 Epoxy/Polysiloxane Part A

Company Name: Key Resin / Flowcrete Phone Number: 4050 Clough Woods Dr. +1 (513)943-4225

4050 Clough Woods Dr. Batavia, OH 45103

Emergency Contact: Chemtrec (USA) (800)424-9300

Chemtrec (International) +1 (703)527-3887

Intended Use: Industrial floor coatings.

2. Hazards Identification

Skin Sensitization, Category 1

Serious Eye Damage/Eye Irritation, Category 2B



GHS Hazard Phrases: H317 - May cause an allergic skin reaction.

H320 - Causes eye irritation.

GHS Precaution Phrases: P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin

irritation or rash occurs, seek medical advice/attention.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation

persists, get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P311 - Call a

POISON CENTER or doctor/physician.

GHS Storage and Disposal

Phrases:

P501 - Dispose of contents/container to local, state, and federal authority requirements.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Potential Health Effects May cause eye irritation. May cause skin irritation. May cause skin sensitization, an

(Acute and Chronic): allergic reaction, which becomes evident on reexposure to this material.

Inhalation: May cause irritating effects.

Skin Contact: Causes skin irritation. May cause sensitization by skin contact.

Eye Contact: Causes eye irritation.

Ingestion: May be harmful if swallowed.

Medical Conditions Generally Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

Aggravated By Exposure:

#570 Epoxy/Polysiloxane Part A

Revision: 07/06/2021

Printed: 07/06/2021

Supersedes Revision: 08/03/2015

3. Composition/Information on Ingredients						
CAS#	Hazardous Components (Chemical Name)	Concentration				
30583-72-3	Hydrogenated dyglycidyl ether of bispenol A	50 %				

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention

immediately.

In Case of Skin Contact: In case of contact, immediately wash skin with soap and copious amounts of water.

Remove contaminated clothing and shoes. Get medical attention if irritation develops or

In Case of Eye Contact: In case of contact with eyes, flush with copious amounts of water for at least 15 minutes.

Assure adequate flushing by separating the eyelids with fingers. Call a physician.

If swallowed, wash out mouth with water provided person is conscious. Call a physician In Case of Ingestion:

immediately. Do not induce vomiting. For further assistance, contact your local Poison

Control Center.

Signs and Symptoms Of

Exposure:

May cause skin, eye, and respiratory irritation. May cause allergic skin reaction.

5. Fire Fighting Measures

> 200.00 C (392.0 F) Method Used: Pensky-Marten Closed Cup Flash Pt:

Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data.

Suitable Extinguishing Media: Dry chemical, CO2, water spray or regular foam.

Do not use a direct water stream, which may spread fire. Unsuitable Extinguishing

Media:

Fire Fighting Instructions: Protective Equipment: Wear self-contained breathing apparatus and protective clothing

to prevent contact with skin and eyes.

Flammable Properties and

Hazards:

Product is not considered a fire hazard. Closed containers may rupture (due to build up

in pressure) when exposed to extreme heat.

6. Accidental Release Measures

Protective Precautions, Protective Equipment and **Emergency Procedures:**

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions: Prevent entry into waterways, sewers, basements or confined areas. PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL. Steps To Be Taken In Case

Material Is Released Or

Spilled:

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the

area.

7. Handling and Storage

Precautions To Be Taken in

Handling:

Provide adequate ventilation. Do not breathe vapor. Do not get in eyes, on skin or on

clothing.

Precautions To Be Taken in

Storing:

Store away from incompatible material. Keep container tightly closed in a dry and

well-ventilated place.

Other Precautions: Wash thoroughly after handling.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format

Page: 2

#570 Epoxy/Polysiloxane Part A

Printed: 07/06/2021 Revision: 07/06/2021

Page: 3

Supersedes Revision: 08/03/2015

8. Exposure Controls/Personal Protection							
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits			
30583-72-3	Hydrogenated dyglycidyl ether of bispenol A	No data.	No data.	No data.			

Respiratory Equipment

(Specify Type):

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection: Safety glasses, or goggles.

Protective Gloves: Nitrile rubber and Neoprene are recommended.

Other Protective Clothing: Where splashing is possible, full chemically resistant protective clothing, safety glasses

or face shield and boots are required.

Engineering Controls

(Ventilation etc.):

Good general ventilation should be sufficient to control airborne levels. Safety shower

and eye bath.

Work/Hygienic/Maintenance

Practices:

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash

thoroughly after handling.

Environmental Exposure

Controls:

Avoid runoff into storm sewers and ditches which lead to waterways. May be hazardous

to the environment if released in large quantities.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Slight odor.

Appearance: Clear to light yellow.

Melting Point:

Boiling Point:

Decomposition Temperature: NE

Autoignition Pt:

NE

No data.

Flash Pt: > 200.00 C (392.0 F) Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: NE UEL: NE

Specific Gravity (Water = 1): ~ 1.135 Density: ~ 9.47 LB/GL

Vapor Pressure (vs. Air or

mm Hg):

NE

Vapor Density (vs. Air = 1): NE
Evaporation Rate: NE
Solubility in Water: No data.

Solubility Notes: Practically insoluble.

#570 Epoxy/Polysiloxane Part A

Printed: 07/06/2021 Revision: 07/06/2021

Page: 4

Supersedes Revision: 08/03/2015

Saturated Vapor

NE

Concentration:

0.0 % by volume.

Percent Volatile: VOC / Volume:

NP

10. Stability and Reactivity

Reactivity:

Strong oxidizing agents.

Stability:

Unstable [] Stable [X]

Conditions To Avoid -

Extreme temperatures. Avoid uncontrolled contact with amines.

Instability:

Incompatibility - Materials To Oxidizing materials, Water.

Avoid:

Hazardous Decomposition Or Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide,

Byproducts:

Phenolics.

Possibility of Hazardous

Will occur [X] Will not occur []

Polymerization:

Conditions To Avoid -

Will not undergo hazardous polymerization in normal storage conditions.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information:

May cause sensitization by skin contact.

Irritation or Corrosion:

Chronic Toxicological

Skin Irritation. Irritating to eyes.

Symptoms related to

May cause rash on skin, and redness in eyes. May cause coughing by inhalation of a

Toxicological mist or spray.

Characteristics:

onaracteristics.

Skin sensitization.

Effects:

12. Ecological Information

General Ecological

Avoid release to the environment. May be hazardous to the environment if released in

Information:

large quantities.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

Not readily biodegradable.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: not reported, unknown.

13. Disposal Considerations

Waste Disposal Method:

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge

substance/product into sewage system.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

GHS format

#570 Epoxy/Polysiloxane Part A

Printed: 07/06/2021 Revision: 07/06/2021

Page: 5

Supersedes Revision: 08/03/2015

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.

DOT Hazard Class: UN/NA Number:

Precautionary Label: Avoid skin and eye contact. May cause eye and skin irritation. May cause skin

sensitization. Wear protective equipment and clothing. Always read MSDS/SDS

before use.

MARINE TRANSPORT (IMDG/IMO):

Not Regulated. IMDG/IMO Shipping Name:

UN Number: Packing Group:

Hazard Class:

IMDG MFAG Number:

IMDG EMS Page: No

AIR TRANSPORT (ICAO/IATA):

Not Regulated. ICAO/IATA Shipping Name:

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
30583-72-3	Hydrogenated dyglycidyl ether of bispenol A	No	No	No

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard 'Hazard Categories' defined [X] Yes [] No Chronic (delayed) Health Hazard

for SARA Title III Sections [] Yes [X] No Fire Hazard

Hazard Rating System:

311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard

[] Yes [X] No Reactive Hazard

16. Other Information

07/06/2021 **Revision Date:**

HEALTH **FLAMMABILITY** 1 **PHYSICAL** 0 PPE Х

HMIS:

Additional Information About CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED

This Product: NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or The information contained in this MSDS is taken from sources believed to be accurate as

Disclaimer: of the date hereof; however the Key Resin Company makes no expressed or implied

warranty in respect to the accuracy of the information or the suitability of the

recommendations, and assumes no liabilities to any user thereof.