#### Part B

1. Product and Company Identification Product Code: 625-RCB **Product Name:** 625 Chemical Resistant Epoxy Hardener Part B Key Resin Company **Company Name: Phone Number:** 4050 Clough Woods Dr. +1 (513)943-4225 Batavia, OH 45103 Chemtrec (USA) **Emergency Contact:** (800)424-9300 Chemtrec (International) +1 (703)527-3887 Intended Use: Industrial floor coatings.

### 2. Hazards Identification

Skin Sensitization, Category 1A Skin Corrosion/Irritation, Category 1B Serious Eye Damage/Eye Irritation, Category 1 Acute Toxicity: Oral, Category 4 Aquatic Toxicity (Acute), Category 1 Aquatic Toxicity (Chronic), Category 1

Danger Warning Warning H317 - May cause an allergic skin reaction. **GHS Hazard Phrases:** H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H302 - Harmful if swallowed. H400 - Very toxic to aquatic life. H410 - Very toxic to aquatic life with long lasting effects. P261 - Avoid breathing dust/mist/vapors/spray. **GHS Precaution Phrases:** P280 - Wear protective gloves/protective clothing/eye protection/face protection. P362+364 - Take off contaminated clothing and wash it before reuse. P273 - Avoid release to the environment. **GHS Response Phrases:** P361 - Remove/Take off immediately all contaminated clothing. P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin irritation or rash occurs, seek medical advice/attention. P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation persists, get medical advice/attention. P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P313 - Get medical advice/attention. P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P314 - Get medical attention/advice if you feel unwell. P391 - Collect spillage. P501 - Dispose of contents/container to local, state, and federal authority requirements. GHS Storage and Disposal Phrases: This material is classified as hazardous under OSHA regulations. OSHA Regulatory Status:

Revision: 06/10/2019 Supersedes Revision: 06/06/2018

Printed: 06/11/2019

#### **SAFETY DATA SHEET** 625 Chemical Resistant Epoxy Hardener Part B

Page: 2 Printed: 06/11/2019 Revision: 06/10/2019 Supersedes Revision: 06/06/2018

Potential Health Effects	Corrosive! Damages skin and eyes.
(Acute and Chronic):	Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.
	Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.
Inhalation:	May cause respiratory irritation.
Skin Contact:	Causes severe skin irritation. Causes skin burns.
Eye Contact:	Corrosive/irritation to eyes. Causes eye burns.
Ingestion:	Harmful if swallowed.

**Medical Conditions Generally** Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies. **Aggravated By Exposure:** 

3. (	Com	oosition/Infor	mation on	Ingredients
------	-----	----------------	-----------	-------------

CAS #	Hazardous Components (Chemical Name)	Concentration
2855-13-2	Isophoronediamine	40 - 60 %
100-51-6	Benzenemethanol	30 - 40 %
84852-15-3	Phenol, 4-nonyl-, branched	10 - 20 %
103-83-3	N,N-Dimethylbenzylamine	1.0 - 10 %
69-72-7	Salicylic acid	1.0 - 10 %

### 4. First Aid Measures

Emergency and First Aid Procedures:	
In Case of Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.
In Case of Skin Contact:	In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.
In Case of Eye Contact:	In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention immediately.
In Case of Ingestion:	If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Get medical attention immediately.
Signs and Symptoms Of Exposure:	Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

#### **SAFETY DATA SHEET** 625 Chemical Resistant Epoxy Hardener

Part B

Page: 3 Printed: 06/11/2019 Revision: 06/10/2019 Supersedes Revision: 06/06/2018

			I ul t D		VISION. 00/00/2016
		5. Fire	Fighting Measur	es	
Flash Pt:		> 200.00 F (93.3 C)	Method Used: Pensk	/-Marten Closed Cup	
Explosive Lin	nits:	LEL: NE	UEL: NE		
Autoignition I	Pt:	No data.			
Suitable Extir	nguishing Media	CO2, dry chemical,	dry sand, alcohol-resista	nt foam.	
Unsuitable Ex Media:	tinguishing	Do not use a direct	water stream, which may	spread fire.	
Fire Fighting	Instructions:	Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.			
Flammable Pı Hazards:	roperties and	Combustible materi	al: may burn but does not	ignite readily.	
		6. Accide	ntal Release Mea	sures	
Protective Pre Protective Eq Emergency P	uipment and	Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.			
Environmenta	al Precautions:	Prevent entry into v	vaterways, sewers, baser	nents or confined areas.	
Steps To Be 1 Material Is Re Spilled:	Faken In Case leased Or	PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL. Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.			
		7. Ha	ndling and Storag	je	
Precautions 1 Handling:	o Be Taken in	Provide adequate v	entilation. Wear all perso	nal protection required in se	ection 8.
Precautions 1 Storing:	o Be Taken in	Keep container tigh incompatible mater		II-ventilated place. Store av	vay from
Other Precau	tions:	Wash thoroughly af	ter handling.		
	8	. Exposure Co	ontrols/Personal	Protection	
CAS #	Partial Chemical	Name	OSHA TWA	ACGIH TWA	Other Limits

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
2855-13-2	Isophoronediamine	No data.	No data.	No data.
100-51-6	Benzenemethanol	No data.	No data.	No data.
84852-15-3	Phenol, 4-nonyl-, branched	No data.	No data.	No data.
103-83-3	N,N-Dimethylbenzylamine	No data.	No data.	No data.
69-72-7	Salicylic acid	No data.	No data.	No data.

Respiratory Equipment	Normally when good engineering controls are used, no respiratory protection is needed.
(Specify Type):	However, if cured product is abraded by sanding or grinding use a NIOSH approved
	air-purifying respirator. Where risk assessment shows air-purifying respirators are
	appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A
	NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or
	canister may be permissible under certain circumstances where airborne concentrations
	are expected to exceed exposure limits. Protection provided by air purifying respirators
	is limited. Use a positive pressure air supplied respirator if there is any potential for an
	uncontrolled release, exposure levels are not known, or any other circumstances where
	air purifying respirators may not provide adequate protection.
Eye Protection:	Safety glasses, or goggles.
Protective Gloves:	Nitrile rubber and Neoprene are recommended.
Other Protective Clothing:	Where splashing is possible, full chemically resistant protective clothing, safety glasses

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

#### SAFETY DATA SHEET 625 Chemical Resistant Epoxy Hardener Part B

Page: 4 Printed: 06/11/2019 Revision: 06/10/2019 Supersedes Revision: 06/06/2018

	Part B Supersedes Revision: 06/06/2018
	or face shield and boots are required.
Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Safety shower
(Ventilation etc.):	and eye bath.
Work/Hygienic/Maintenance	Wash contaminated clothing before reuse. Discard contaminated shoes. Wash
Practices:	thoroughly after handling.
Environmental Exposure	Avoid runoff into storm sewers and ditches which lead to waterways.
Controls:	
	9. Physical and Chemical Properties
Physical States:	[]Gas [X]Liquid []Solid
Appearance and Odor:	Odor: amine-like.
	Appearance: Liquid. amber.
Melting Point:	NE
Boiling Point:	NE
Decomposition Temperature:	NE
Autoignition Pt:	No data.
Flash Pt:	> 200.00 F (93.3 C) Method Used: Pensky-Marten Closed Cup
Explosive Limits:	LEL: NE UEL: NE
Specific Gravity (Water = 1):	-
Density:	~ .903 ~ 8.2 LB/GL
Vapor Pressure (vs. Air or	NE
mm Hg):	
Vapor Density (vs. Air = 1):	NE
Evaporation Rate:	NE
Solubility in Water:	Soluble
Saturated Vapor	NE
Concentration:	
Percent Volatile:	N.A.
VOC / Volume:	NP
	10. Stability and Reactivity
Reactivity:	Avoid: acids, Avoid uncontrolled contact with isocyanates. Avoid: Uncontrolled reactions
	with epoxies.
Stability:	Unstable [ ] Stable [ X ]
Conditions To Avoid -	Extreme temperatures.
Instability:	
•	Avoid strong acids, bases, and oxidizing agents.
	r Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide.
Byproducts:	
	Will occur [ ] Will not occur [ X ]
Possibility of Hazardous	
Possibility of Hazardous Polymerization:	
-	Will not undergo hazardous polymerization in normal storage conditions.

## **SAFETY DATA SHEET** 625 Chemical Resistant Epoxy Hardener

Part B

Page: 5 Printed: 06/11/2019 Revision: 06/10/2019 Supersedes Revision: 06/06/2018

	11. Toxicological Information
Toxicological Information:	May cause sensitization by skin contact.
Irritation or Corrosion:	Corrosive! Damages skin and eyes.
Symptoms related to	May cause sensitization by skin contact. May cause skin irritation or burns.
Toxicological	Can cause eye irritation or burns.
Characteristics:	
Chronic Toxicological	Skin sensitization.
Effects:	
	12. Ecological Information
General Ecological	Avoid release to the environment. Do not empty into drains. May be hazardous to the
Information:	environment if released in large quantities.
Results of PBT and vPvB	No data available.
assessment:	
Persistence and Degradability:	Not readily biodegradable.
Bioaccumulative Potential:	
	No data available.
Mobility in Soil:	not reported, unknown.
	13. Disposal Considerations
Waste Disposal Method:	Incinerate or dispose of unused material, residues and containers in a licensed facility
	accordance with all applicable local, state and federal regulations. Do not discharge
	substance/product into sewage system.
	14. Transport Information
LAND TRANSPORT (US DOT)	•
	ne: CAUSTIC ALKALI LIQUID, N.O.S. (Contains Nonyl Phenol, Modified Cycloaliphat Amines)
DOT Hazard Class:	8 CORROSIVE
UN/NA Number:	UN1719 Packing Group: III
Precautionary Label:	Corrosive! Damages skin and eyes. May cause sensitization by skin contact. May
•	harmful if swallowed.
	CORROSWE
	8
MARINE TRANSPORT (IMDG	×//MO):
IMDG/IMO Shipping Name	-
	Amines) MARINE POLLUTANT.
UN Number:	1719 Packing Group: III
Hazard Class:	8 - CORROSIVE
IMDG EMS Number:	FA,SB IMDG MFAG Number:
IMDG EMS Page:	Yes
AIR TRANSPORT (ICAO/IATA	A):
ICAO/IATA Shipping Nam	e: CAUSTIC ALKALI LIQUID, N.O.S. (Contains Nonyl Phenol, Modified Cycloaliphat Amines)
IMDG EMS Page: AIR TRANSPORT (ICAO/IATA	Yes A): e: CAUSTIC ALKALI LIQUID, N.O.S. (Contains Nonyl Phenol, Modified Cycloaliph

# **SAFETY DATA SHEET** 625 Chemical Resistant Epoxy Hardener

Part B

Page: 6 Printed: 06/11/2019 Revision: 06/10/2019 Supersedes Revision: 06/06/2018

		15. Regulato	ry Informatio	on	
EPA SARA (Sı	uperfund Amendm	ents and Reauthorization Act	of 1986) Lists		
CAS #	Hazardous Com	ponents (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
2855-13-2	Isophoronediamii	ne	No	No	No
100-51-6	Benzenemethand	bl	No	No	No
84852-15-3	Phenol, 4-nonyl-,	branched	No	No	No
103-83-3	N,N-Dimethylben	zylamine	No	No	No
69-72-7	Salicylic acid		No	No	No
for SARA Titl 311/312 as in	e III Sections dicated:	[]Yes [X] No Fire Hazard []Yes [X] No Sudden Re []Yes [X] No Reactive H	lease of Pressure	Hazard	
Regulatory In			ntrol Act): All com	ponents are listed	l or exempt.
Revision Date	e:	06/10/2019			
Hazard Ratin	HMIS:	HEALTH3FLAMMABILITY1PHYSICAL0PPEX			
Additional Inf This Product:		CA=CIRCA NA=NOT AVAI	LABLE NE=NOT	ESTABLISHED	
Company Pol			=PROPRIETARY	TS=TRADE SEC	CRET ?=UNKNOWN.