SAFETY DATA SHEET 630/633 Epoxy Novolac Coating- Part A (Clear)

	HEALTH2FLAMMABILITY1PHYSICAL0PPEX	Printed: 06/11/2015 Revision: 06/11/2015 Supersedes Revision: 05/14/2015			
1. Pr	oduct and Company	Identification			
Product Code:	630/633-CLEAR				
Product Name:	630/633 Epoxy Novolac Coa	ting- Part A (Clear)			
Trade Name:	630/633 Epoxy Novolac Coa	630/633 Epoxy Novolac Coating- Part A (Clear)			
Manufacturer Information					
Company Name:	Key Resin Company				
	4050 Clough Woods Dr.				
	Batavia, OH 45103				
Phone Number:	+1 (513)943-4225				
Emergency Contact:	Chemtrec (USA)	(800)424-9300			
Alternate Emergency Contact:	Chemtrec (International)	+1 (703)527-3887			
Intended Use:	Industrial floor coatings.				
	2. Hazards Identifi	cation			

GHS Classification	Placard	Key word	GHS hazard phrase	
Skin Corrosion/Irritation, Category 2	Exclamation point	Warning	Causes skin irritation	
Serious Eye Damage/Eye Irritation, Category 2B	none	Warning	Causes eye irritation	
Skin Sensitization, Category 1B	Exclamation point	Warning	May cause an allergic skin reaction	

GHS Hazard Phrases

H315 - Causes skin irritation. H320 - Causes eye irritation.

H335 - May cause respiratory irritation.

H303 - May be harmful if swallowed.

GHS Precaution Phrases

P280 - Wear protective gloves/protective clothing/eye protection.

P261 - Avoid breathing mist/vapours. P264 - Wash hands thoroughly after handling.

GHS Response Phrases

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P332+313 - If skin irritation occurs, get medical advice/attention.

P362 - Take off contaminated clothing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313 - If eye irritation persists, get medical advice/attention.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

GHS Storage and Disposal Phrases

P403+235 - Store in cool/well-ventilated place. P404 - Store in a closed container.

Potential Health Effects (Acute and Chronic)

Causes skin and eye irritation. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.

Inhalation

May cause respiratory irritation.

Skin Contact

Causes skin irritation. May cause an allergic skin reaction.

Eye Contact

May cause eye irritation.

Ingestion

May be harmful if swallowed.

Recommended Exposure Limits

Not established.

Medical Conditions Generally Aggravated By Exposure

May cause rash on skin, and redness in eyes. May cause coughing by inhalation of a mist or spray.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients					
Hazardous Components (Chemical Name) CAS # Concentration					
1. Phenol-Formaldehyde Polymer	28064-14-4	80 - 100 %			
2. Benzenemethanol	100-51-6	1.0 - 10 %			
3. Phenol, 4-nonyl-, branched 84852-15-3 1.0 - 8.0 %					
4. First Aid Measures					

Emergency and First Aid Procedures

In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Call a physician immediately. Do not induce vomiting. For further assistance, contact your local Poison Control Center.

Signs and Symptoms Of Exposure

Moderate irritation effect.

	5. Fire Fighting Measures				
Flash Pt:	> 200.00 F Method Used: Pensky-Marten Closed Cup				
Explosive Limits:	LEL: NE UEL: NE				
Autoignition Pt:	No data available.				

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards

Product is not considered a fire hazard. Closed containers may rupture (due to build up in pressure) when exposed to extreme heat.

SAFETY DATA SHEET

630/633 Epoxy Novolac Coating- Part A (Clear)

Page: 3 Printed: 06/11/2015 Revision: 06/11/2015 Supersedes Revision: 05/14/2015

Hazardous Combustion Products

In a fire, product may produce the following: Carbon monoxide, Carbon dioxide, Phenolics.

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam.

Unsuitable Extinguishing Media

Do not use a direct water stream, which may spread fire.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

7. Handling and Storage

Hazard Label Information:

Avoid contact with skin and eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist. Store in a closed container.

Precautions To Be Taken in Handling

Provide adequate ventilation. Do not breathe vapor. Do not get in eyes, on skin or on clothing.

Precautions To Be Taken in Storing

Keep container tightly closed in a dry and well-ventilated place.

Other Precautions

Wash thoroughly after handling.

8. Exposure Controls/Personal Protection							
Hazardous Components (Chemical Name) CAS # OSHA PEL ACGIH TLV Other Limits							
1. Phenol-Formaldehyde Polymer	28064-14-4	No data.	No data.	No data.			
2. Benzenemethanol	100-51-6	No data.	No data.	No data.			
3. Phenol, 4-nonyl-, branched 84852-15-3 No data. No data. No data.							
Protocilies Environment Operations I I also be before a file							

Protective Equipment Summary - Hazard Label Information:

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

Respiratory Equipment (Specify Type)

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection

Safety glasses, or goggles.

Protective Gloves

Nitrile rubber and Neoprene are recommended.

SAFETY DATA SHEET 630/633 Epoxy Novolac Coating- Part A (Clear)

Page: 4 Printed: 06/11/2015 Revision: 06/11/2015 Supersedes Revision: 05/14/2015

Other Protective Clothing

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

Engineering Controls (Ventilation etc.)

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Environmental Exposure Controls

Avoid runoff into storm sewers and ditches which lead to waterways.

9. P	hysical and Chemical Properties
Physical States:	[]Gas [X]Liquid []Solid
Melting Point:	NE
Boiling Point:	NE
Decomposition Temperature:	NE
Autoignition Pt:	No data.
Flash Pt:	> 200.00 F Method Used: Pensky-Marten Closed Cup
Explosive Limits:	LEL: NE UEL: NE
Specific Gravity (Water = 1):	~ 1.167
Density:	~ 9.73 LB/GL
Vapor Pressure (vs. Air or mm Hg):	NE
Vapor Density (vs. Air = 1):	NE
Evaporation Rate:	NE
Solubility in Water:	NP
Percent Volatile:	0.0 % by volume.
VOC / Volume:	NP
HAP / Volume:	NP
Saturated Vapor Concentration:	NE
Appearance and Odor	
Slight odor.	
Appearance: Liquid. Clear.	

10. Stability and Reactivity					
Stability:	Unstable []	Stable [X]			
Reactivity					
Avoid: acids, alkalis, oxidizing	gagents.				
Conditions To Avoid - Instability					
Extreme temperatures.					
Incompatibility - Materials To Avoid					
Avoid strong acids, bases, and	oxidizing agents. Av	void contact with amines.			
Hazardous Decomposition Or Byp	roducts				
Thermal decomposition may p	roduce smoke, carbo	on monoxide, carbon dioxide, and phenolics.			
Possibility of Hazardous	Will occur []	Will not occur [X]			
Polymerization:					
Conditions To Avoid - Hazardous	Reactions				

Will not undergo hazardous polymerization in normal storage conditions.

11. Toxicological Information

Toxico	l <mark>ogi</mark>	cal In	formation	

Skin sensitization.

Chronic Toxicological Effects

May cause sensitization by skin contact.

Irritation or Corrosion

Skin Irritation. Irritating to eyes.

Symptoms related to Toxicological Characteristics

May cause redness, rash on skin. May cause slight skin irritation or skin sensitization. May be slightly irritating to eyes and respiratory system.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Phenol-Formaldehyde Polymer	28064-14-4	n.a.	n.a.	n.a.	n.a.
2. Benzenemethanol	100-51-6	n.a.	n.a.	n.a.	n.a.
3. Phenol, 4-nonyl-, branched	84852-15-3	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information

Avoid release to the environment. May be hazardous to the environment if released in large quantities.

Results of PBT and vPvB assessment

No data available.

Persistence and Degradability

Not readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

not reported, unknown.

13. Disposal Considerations

Waste Disposal Method

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

14. Transport Information

	14. Transport information
LAND TRANSPORT (US DOT)	
DOT Proper Shipping Name	(Non-Bulk)
	Not Regulated.
	(Bulk)
	Environmentally hazardous substance, liquid, n.o.s. (EPOXY NOVOLAC
	RESIN)
	NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do
	not apply to non-bulk packagings transported by motor vehicles, rail cars or
	aircraft.
DOT Hazard Class:	9
DOT Hazard Label:	CLASS 9
UN/NA Number:	UN3082
Packing Group:	III

SAFETY DATA SHEET 630/633 Epoxy Novolac Coating- Part A (Clear)

AIR TRANSPORT (ICAO/IATA)				·			
ICAO/IATA Shipping Name	(Non-Bulk) Not Regulated.						
	(Bulk) Environmentally hazardous substance, liquid, n.o.s. (EPOXY NOVOLAC RESIN) MARINE POLLUTANT.						
		NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.					
UN Number:	3082						
Hazard Class:	9 - CLASS 9						
Packing Group:	Ш						
MARINE TRANSPORT (IMDG/IMO)							
IMDG/IMO Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (EPOXY NOVOLAC RESIN) MARINE POLLUTANT.						
UN Number:	3082						
Hazard Class:	9 - CLASS 9						
Packing Group:	Ш						
IMDG EMS Number:	FA,SF						
Marine Pollutant:	Yes						
	15. Regula	atory Inform	nation				
US EPA SARA Title III							
Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110		
1. Phenol-Formaldehyde Polymer	28064-14-4	No	No	No	No		
2. Benzenemethanol	100-51-6 No No No						
3. Phenol, 4-nonyl-, branched	84852-15-3 No No No No						
Regulatory Information SARA Section 311/312: Acute F	Joalth Hazard						
			•				
	16. Oth	er Informat	tion				

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or Disclaimer

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however the Key Resin Company makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof. **Revision Date:** 06/11/2015

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.