Hardeners - Part B

1. Product and Company Identification Product Code: 783-RCB-FCB Product Name: 783 Novolac Joint Filler Regular/Fast Cure Hardeners - Part B Key Resin Company **Company Name:** Phone Number: 4050 Clough Woods Dr. +1 (513)943-4225 Batavia, OH 45103 Chemtrec (USA) (800)424-9300 **Emergency Contact:** Chemtrec (International) +1 (703)527-3887 Industrial floor coatings. Intended Use:

#### 2. Hazards Identification

Acute Toxicity: Oral, Category 4 Acute Toxicity: Skin, Category 4 Skin Corrosion/Irritation, Category 1B Serious Eye Damage/Eye Irritation, Category 1 Skin Sensitization, Category 1 Aquatic Toxicity (Acute), Category 1 Aquatic Toxicity (Chronic), Category 1

₩,

| GHS Hazard Phrases:      | H302 - Harmful if swallowed.  |
|--------------------------|---|
| GHS Hazard Phrases:      | H312 - Harmful in contact with skin.  |
|                          | H314 - Causes severe skin burns and eye damage.   |
|                          | H318 - Causes serious eye damage.   |
|                          | H317 - May cause an allergic skin reaction.   |
|                          | H400 - Very toxic to aquatic life.  |
|                          | H410 - Very toxic to aquatic life with long lasting effects.  |
| GHS Precaution Phrases:  | P262 - Do not get in eyes, on skin, or on clothing.   |
|                          | P280 - Wear protective gloves/protective clothing/eye protection/face protection.   |
|                          | P260 - Do not breathe dust/fume/gas/mist/vapours/spray.   |
|                          | P273 - Avoid release to the environment.  |
|                          | P103 - Read label before use.   |
| GHS Response Phrases:    | <ul> <li>P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. P363 - Wash contaminated clothing before reuse. P333+313 - If skin irritation or rash occurs, seek medical advice/attention.</li> <li>P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation persists, get medical advice/attention.</li> <li>P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P311 - Call a POISON CENTER or doctor/physician.</li> <li>P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P342+311 - If experiencing respiratory symptoms call a POISON CENTER or doctor/physician.</li> </ul> |
|                          | P391 - Collect spillage.  |
| GHS Storage and Disposal | P501 - Dispose of contents/container to local, state, and federal authority requirements.   |
| Phrases:                 | P405 - Store locked up.   |

Printed: 06/11/2019

| OSHA Regulatory Status:                          | This material is classified as hazardous under OSHA regulations.  |
|--|---|
| Potential Health Effects<br>(Acute and Chronic): | May cause skin irritation or burns. May cause respiratory tract irritation. Can cause severe eye irritation.  |
| Inhalation:                                      | Can cause severe respiratory irritation.  |
| Skin Contact:                                    | Contact with substance may cause severe burns to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.   |
| Eye Contact:                                     | Corrosive/irritation to eyes. Causes eye burns.   |
| Ingestion:                                       | Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. Aspiration hazard if swallowed. Can enter lungs and cause damage. |

**Medical Conditions Generally** Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies. **Aggravated By Exposure:** 

| 3. Composition/Information on Ingredients |                                      |               |  |
|---|--------------------------------------|---------------|--|
| CAS #                                     | Hazardous Components (Chemical Name) | Concentration |  |
| 84852-15-3                                | Phenol, 4-nonyl-, branched           | 45 - 60 %     |  |
| 9046-10-0                                 | *Poly(oxy(methyl-1,2-ethanediyl)     | 15 - 25 %     |  |
| 1317-65-3                                 | Limestone                            | 5.0 - 20 %    |  |
| NA  | Aliphatic Amines                     | 1.0 - 10 %    |  |
| 112945-52-5                               | Silica, amorphous treated            | 1.0 - 5.0 %   |  |

|  | 4. First Aid Measures  |
|--|--|
| Emergency and First Aid<br>Procedures: |  |
| In Case of Inhalation:                 | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.                                     |
| In Case of Skin Contact:               | In case of contact, immediately wash skin with soap and copious amounts of water.<br>Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.   |
| In Case of Eye Contact:                | In case of contact with eyes, flush with copious amounts of water for at least 15 minutes.<br>Assure adequate flushing by separating the eyelids with fingers. Get medical attention<br>immediately.                                 |
| In Case of Ingestion:                  | If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Get medical attention immediately. |
| Signs and Symptoms Of<br>Exposure:     | Eyes: Symptoms may include discomfort or pain, excess blinking and tear production,<br>with marked redness and swelling of the conjunctiva.<br>Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying,       |
|  | defatting and cracking of the skin.<br>Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and<br>cough.  |
|  |  |
|  |  |

## SAFETY DATA SHEET 783 Novolac Joint Filler Regular/Fast Cure

Hardeners - Part B

Page: 3 **re** Printed: 06/11/2019 Revision: 06/10/2019 Supersedes Revision: 07/07/2016

|   | 5. Fire Fighting Measures  |  |  |  |
|---|--|--|--|--|
| Flash Pt:   | > 200.00 F (93.3 C) Method Used: Closed Cup  |  |  |  |
| Explosive Limits:   | LEL: NE UEL: NE  |  |  |  |
| Autoignition Pt:  | No data.   |  |  |  |
| Suitable Extinguishing Media:CO2, dry chemical, dry sand, alcohol-resistant foam. |  |  |  |  |
| Unsuitable Extinguishing<br>Media:  | Do not use a direct water stream, which may spread fire.   |  |  |  |
| Fire Fighting Instructions:   | Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.   |  |  |  |
| Flammable Properties and<br>Hazards:  | Combustible material: may burn but does not ignite readily.  |  |  |  |
|   | 6. Accidental Release Measures   |  |  |  |
| Protective Precautions,<br>Protective Equipment and<br>Emergency Procedures:      | Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required. |  |  |  |
| Environmental Precautions:  | Prevent entry into waterways, sewers, basements or confined areas.   |  |  |  |
| Steps To Be Taken In Case   | PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.   |  |  |  |
| Material Is Released Or<br>Spilled:   | Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.   |  |  |  |
|   | 7. Handling and Storage  |  |  |  |
| Precautions To Be Taken in Handling:  | Provide adequate ventilation. Wear all personal protection required in section 8.  |  |  |  |
| Precautions To Be Taken in<br>Storing:  | Keep container tightly closed in a dry and well-ventilated place. Store away from incompatible material.   |  |  |  |
| Other Precautions:  | Read product SDS and all labels before use. Follow all MSDS/label precautions even after container is emptied because they may retain product residues.                              |  |  |  |
| 0   | Experies Controls/Dersonal Drotaction  |  |  |  |

### 8. Exposure Controls/Personal Protection

| CAS #       | Partial Chemical Name            | OSHA TWA                           | ACGIH TWA | Other Limits |
|-------------|----------------------------------|------------------------------------|-----------|--------------|
| 84852-15-3  | Phenol, 4-nonyl-, branched       | No data.                           | No data.  | No data.     |
| 9046-10-0   | *Poly(oxy(methyl-1,2-ethanediyl) | No data.                           | No data.  | No data.     |
| 1317-65-3   | Limestone                        | PEL: 15 (dust); 5 (resp.)<br>mg/m3 | No data.  | No data.     |
| NA          | Aliphatic Amines                 | No data.                           | No data.  | No data.     |
| 112945-52-5 | Silica, amorphous treated        | No data.                           | No data.  | No data.     |

| <b>Respiratory Equipment</b>   | Normally when good engineering controls are used, no respiratory protection        | is needed. |
|--------------------------------|--|------------|
| (Specify Type):                | However, if cured product is abraded by sanding or grinding use a NIOSH app        | proved     |
|                                | air-purifying respirator. Where risk assessment shows air-purifying respirators    | are        |
|                                | appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A        |            |
|                                | NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge       |            |
|                                | canister may be permissible under certain circumstances where airborne cond        |            |
|                                | are expected to exceed exposure limits. Protection provided by air purifying r     | · ·        |
|                                | is limited. Use a positive pressure air supplied respirator if there is any potent |            |
|                                | uncontrolled release, exposure levels are not known, or any other circumstand      | ces where  |
|                                | air purifying respirators may not provide adequate protection.                     |            |
| Eye Protection:                | Safety glasses, or goggles.  |            |
| Protective Gloves:             | Nitrile rubber and Neoprene are recommended.                                       |            |
| Licensed to Key Resin Company: | MIRS MSDS, (c) A V Systems, Inc.   | GHS format |

|   | SAFETY DATA SHEET   |  |  |  |
|---|---|--|--|--|
|   | 783 Novolac Joint Filler Regular/Fast Cure Printed: 06/11/2019<br>Revision: 06/10/2019  |  |  |  |
|   | Hardeners - Part B Supersedes Revision: 07/07/201   |  |  |  |
| Other Protective Clothing:                  | Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required. |  |  |  |
| Engineering Controls (Ventilation etc.):    | Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.                             |  |  |  |
| Work/Hygienic/Maintenance<br>Practices:     | Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.                              |  |  |  |
| Environmental Exposure<br>Controls:         | Avoid runoff into storm sewers and ditches which lead to waterways.   |  |  |  |
|   | 9. Physical and Chemical Properties   |  |  |  |
| Physical States:                            | []Gas [X]Liquid []Solid   |  |  |  |
| Appearance and Odor:                        | Odor: amine-like.   |  |  |  |
|   | Appearance: Liquid. amber.  |  |  |  |
| Melting Point:                              | NE  |  |  |  |
| Boiling Point:                              | NE  |  |  |  |
| Decomposition Temperature:                  |   |  |  |  |
| Autoignition Pt:                            | No data.  |  |  |  |
| Flash Pt:                                   |   |  |  |  |
|   |   |  |  |  |
| Explosive Limits:                           | LEL: NE UEL: NE   |  |  |  |
| Specific Gravity (Water = 1):               |   |  |  |  |
| Density:                                    | ~ 8.93 LB/GL  |  |  |  |
| Vapor Pressure (vs. Air or<br>mm Hg):       | NE  |  |  |  |
| Vapor Density (vs. Air = 1):                | NE  |  |  |  |
| Evaporation Rate:                           | NE  |  |  |  |
| Solubility in Water:                        | NE  |  |  |  |
| Saturated Vapor                             | NE  |  |  |  |
| Concentration:                              |   |  |  |  |
| Percent Volatile:                           | N.A.  |  |  |  |
| VOC / Volume:                               | NP  |  |  |  |
|   | 10. Stability and Reactivity  |  |  |  |
| Reactivity:                                 | Avoid: acids, alkalis, oxidizing agents.  |  |  |  |
| Stability:                                  | Unstable [ ] Stable [ X ]   |  |  |  |
| Conditions To Avoid -<br>Instability:       | Extreme temperatures.   |  |  |  |
| -   | Avoid: acids, alkalis, oxidizing agents. ammonia. aldehydes.  |  |  |  |
| Hazardous Decomposition O<br>Byproducts:    | r Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, and phenolics.  |  |  |  |
| Possibility of Hazardous                    | Will occur [ ] Will not occur [ X ]   |  |  |  |
| Possibility of Hazardous<br>Polymerization: |   |  |  |  |

#### SAFETY DATA SHEET 783 Novolac Joint Filler Regular/Fast Cure

Hardeners - Part B

**11. Toxicological Information** May cause sensitization by skin contact. Toxicological Information: Corrosive! Damages skin and eyes. Irritation or Corrosion: Symptoms related to Skin: Contact with substance may cause severe burns to skin. Symptoms may include Toxicological redness, edema, drying, defatting and cracking of the skin. Characteristics: Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Permanent eye damage including blindness could result. Inhalation: Inhalation of vapors/fumes causes respiratory irritation with throat discomfort, coughing or difficulty breathing. May cause sensitization by skin contact. Sensitization: Chronic Toxicological No data available. Effects: **12. Ecological Information** General Ecological Avoid release to the environment. Do not empty into drains. May be hazardous to the Information: environment if released in large quantities. Results of PBT and vPvB No data available. assessment: Persistence and Not readily biodegradable. Degradability: **Bioaccumulative Potential:** No data available. Mobility in Soil: not reported, unknown. **13. Disposal Considerations** Waste Disposal Method: Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system. 14. Transport Information LAND TRANSPORT (US DOT): DOT Proper Shipping Name: CAUSTIC ALKALI LIQUID, N.O.S. (Aliphatic Amines) (Nonylphenol) MARINE POLLUTANT. Marine Pollutant(s): Nonylphenol. NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft. () DOT Hazard Class: 8 CORROSIVE **UN/NA Number:** Ш UN1719 Packing Group: Precautionary Label: Corrosive! Damages skin and eyes. Avoid skin and eye contact. May cause eye and skin irritation. May cause skin sensitization. Wear protective equipment and clothing. Always read MSDS/SDS before use.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

Page: 5

Revision: 06/10/2019 Supersedes Revision: 07/07/2016

Printed: 06/11/2019

|                         |  | SAFET<br>783 Novolac Joint   | Y DATA SHE<br>Filler Regula                 |                    | Page: 6<br>Printed: 06/11/2019<br>Revision: 06/10/2019 |
|-------------------------|--|--|---|--------------------|--|
|                         |  | Harde  | eners - Part B                              | Supe               | ersedes Revision: 07/07/2016                           |
| MARINE TRA              | NSPORT (IMDG/IM  | 10):   |   |                    |  |
| IMDG/IMO Shipping Name: |  | CAUSTIC ALKALI LIQUID, N.O.S. (Aliphatic Amines) (Nonylphenol) MARINE<br>POLLUTANT.  |   |                    |  |
| UN Number:              |  | Marine Pollutant(s): Nonylphenol.<br>1719 <b>Packing Group:</b>  |   |                    | II   |
| Hazard C                | lass:<br>S Number:                                       | 8 - CORROSIVE<br>FA,SB IMDG MFAG Number:   |   | AG Number:         |  |
| IMDG EM                 |  |  |   |                    | Yes  |
|                         | ORT (ICAO/IATA):   |  |   |                    |  |
|                         | A Shipping Name:   | CAUSTIC ALKALI LIQUID, N.O.S. (Aliphatic Amines) (Nonylphenol) MARINE POLLUTANT.   |   |                    |  |
|                         |  | Marine Pollutant(s): Non   | ylphenol.                                   |                    |  |
|                         |  | NOTE: Marine Pollutants<br>apply to non-bulk package   |   |                    |  |
|                         |  | 15. Regulator  | <u> </u>                                    | -                  |  |
| EPA SARA (Su            | perfund Amendment  | s and Reauthorization Act  | of 1986) Lists                              |                    |  |
| CAS #                   | Hazardous Compor   | ents (Chemical Name)   | S. 302 (EHS)                                | S. 304 RQ          | S. 313 (TRI)   |
| 84852-15-3              | Phenol, 4-nonyl-, bra                                    | nched  | No  | No                 | No   |
| 9046-10-0               | *Poly(oxy(methyl-1,2                                     | -ethanediyl)   | No  | No                 | No   |
| 1317-65-3               | Limestone  |  | No  | No                 | No   |
| NA                      | Aliphatic Amines   |  | No  | No                 | No   |
| 112945-52-5             | Silica, amorphous tre                                    | ated   | No  | No                 | No   |
|                         | ories' defined [X]<br>e III Sections [ ]<br>dicated: [ ] | Yes       No       Acute (imm)         Yes       No       Chronic (de)         Yes       No       Fire Hazard         Yes       No       Sudden Rei         Yes       No       Reactive Hazard | layed) Health Haz<br>l<br>lease of Pressure | zard               |  |
| Regulatory In           | formation: TS  | SCA (Toxic Substance Co  | ntrol Act): All com                         | ponents are listed | l or exempt.   |

# SAFETY DATA SHEET 783 Novolac Joint Filler Regular/Fast Cure

Hardeners - Part B

**16. Other Information** 06/10/2019 **Revision Date:** Hazard Rating System: HEALTH 3 FLAMMABILITY 1 PHYSICAL 0 PPE х HMIS: Additional Information About CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN. This Product: The information contained in this MSDS is taken from sources believed to be accurate as Company Policy or Disclaimer: of the date hereof; however the Key Resin Company makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof.

Page: 7

Revision: 06/10/2019 Supersedes Revision: 07/07/2016

Printed: 06/11/2019