Printed: 10/12/2016 Revision: 10/12/2016

Supersedes Revision: 07/02/2015

**Phone Number:** 

(800)424-9300

+1 (513)943-4225

1. Product and Company Identification

Product Code: 803-CLEAR

Product Name:803 AcH Acrylic SealerTrade Name:803 AcH Acrylic SealerCompany Name:Key Resin Company

oniparty Name. Rey Resili Company

4050 Clough Woods Dr.

Batavia, OH 45103

Emergency Contact: Chemtrec (USA)

Chemtrec (International) +1 (703)527-3887

Intended Use: Industrial floor coatings.

2. Hazards Identification

Skin Corrosion/Irritation, Category 3

Serious Eye Damage/Eye Irritation, Category 2B

**GHS Hazard Phrases:** H316 - Causes mild skin irritation.

H320 - Causes eye irritation.

GHS Precaution Phrases: P281 - Use personal protective equipment as required.

P262 - Do not get in eyes, on skin, or on clothing. P264 - Wash hands thoroughly after handling.

P273 - Avoid release to the environment.

GHS Response Phrases: P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation

persists, get medical advice/attention.

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin

irritation or rash occurs, seek medical advice/attention.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P311 - Call a

POISON CENTER or doctor/physician.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P314 - Get medical attention/advice if you feel unwell.

**GHS Storage and Disposal** 

P403+235 - Store in cool/well-ventilated place. P401 - Store between 45-85 degrees

Phrases:

Inhalation:

Fahrenheit.

**OSHA Regulatory Status:** This material is classified as hazardous under OSHA regulations.

Potential Health Effects

May cause slight eye irritation. May cause slight skin irritation.

(Acute and Chronic):

Prolonged or excessive inhalation may cause respiratory tract irritation. May cause

headaches and dizziness.

**Skin Contact:** May cause skin irritation. **Eye Contact:** May cause eye irritation.

**Ingestion:** May be harmful if swallowed and enters airways.

Medical Conditions Generally Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

Aggravated By Exposure:

#### 3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
NA	Epoxy-Acrylic Copolymer	10 - 20 %
NA	Styrene-Acrylic Copolymer	1.0 - 10 %
29911-28-2	2-Propanol, 1-(2-butoxy-1-methylethoxy)-	1.0 - 10 %
84-74-2	Dibutyl phthalate	<1.0 %

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Page: 1

Page: 2

Printed: 10/12/2016

Revision: 10/12/2016

Supersedes Revision: 07/02/2015

#### 4. First Aid Measures

Emergency and First Aid

Procedures:

**In Case of Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention

immediately.

In Case of Skin Contact: In case of contact, immediately wash skin with soap and copious amounts of water.

Remove contaminated clothing and shoes. Get medical attention if irritation develops or

persists.

In Case of Eye Contact: In case of contact with eyes, flush with copious amounts of water for at least 15 minutes.

Assure adequate flushing by separating the eyelids with fingers. Call a physician.

In Case of Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician

immediately. For further assistance, contact your local Poison Control Center.

Signs and Symptoms Of

Exposure:

Mild irritation effect.

#### 5. Fire Fighting Measures

Flash Pt: NA Method Used: Not Applicable Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data.

Suitable Extinguishing Media:Will not support combustion.

Unsuitable Extinguishing Will not support combustion.

Media:

Fire Fighting Instructions: Protective Equipment: Wear self-contained breathing apparatus and protective clothing

to prevent contact with skin and eyes. Use water spray to cool unopened containers.

Flammable Properties and

Hazards:

Product will not support combustion as supplied. Product is not considered a fire hazard. Closed containers may rupture (due to build up in pressure) when exposed to extreme

heat.

#### 6. Accidental Release Measures

Protective Precautions, Protective Equipment and Emergency Procedures: Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves.

Environmental Precautions: Steps To Be Taken In Case

Prevent entry into waterways, sewers, basements or confined areas. PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Material Is Released Or

Evacuate area. Absorb with sand or vermiculite and place in closed containers for

disposal. Ventilate the area.

#### 7. Handling and Storage

Precautions To Be Taken in

Handling:

Spilled:

Provide adequate ventilation. Do not get in eyes, on skin or on clothing.

Precautions To Be Taken in

Keep from freezing. Keep container closed when not in use. Store at temperatures

Storing: between 45F-85F.

Other Precautions: Read product SDS and all labels before use.

# 8. Exposure Controls/Personal Protection

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Page: 3 Printed: 10/12/2016 Revision: 10/12/2016

Supersedes Revision: 07/02/2015

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Epoxy-Acrylic Copolymer	No data.	No data.	No data.
NA	Styrene-Acrylic Copolymer	No data.	No data.	No data.
29911-28-2	2-Propanol, 1-(2-butoxy-1-methylethoxy)-	No data.	No data.	No data.
84-74-2	Dibutyl phthalate	PEL: 5 mg/m3	TLV: 5 mg/m3	No data.

Respiratory Equipment

(Specify Type):

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**Eye Protection:** Safety glasses, or goggles.

**Protective Gloves:** Nitrile rubber and Neoprene are recommended.

Other Protective Clothing: Where splashing is possible, full chemically resistant protective clothing, safety glasses

or face shield and boots are required.

**Engineering Controls** 

(Ventilation etc.):

Good general ventilation should be sufficient to control airborne levels. Safety shower

and eye bath.

Work/Hygienic/Maintenance

Practices:

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash

thoroughly after handling.

**Environmental Exposure** 

Controls:

Avoid release to the environment. Avoid runoff into storm sewers and ditches which lead

to waterways.

# 9. Physical and Chemical Properties

Physical States: [ ] Gas [ X ] Liquid [ ] Solid

Appearance and Odor: Milky. Faint.

Melting Point: No data.

**Boiling Point:** 212.00 F (100.0 C)

Autoignition Pt: No data.

Flash Pt: NA Method Used: Not Applicable Explosive Limits: LEL: NE UEL: NE

Specific Gravity (Water = 1): 1.02

Density: ~ 8.5

Vapor Pressure (vs. Air or NE

mm Hg):

Vapor Density (vs. Air = 1): NE
Evaporation Rate: NE

Evaporation Rate: NE
Solubility in Water: Soluble
Solubility Notes: Water soluble.

Saturated Vapor

Concentration:

Percent Volatile: ~ 80 % by weight.

**VOC / Volume:** 90.0000 G/L

Printed: 10/12/2016 Revision: 10/12/2016

Supersedes Revision: 07/02/2015

10. Stability and Reactivity

Moisture reactive substances. Reactivity: Stability: Unstable [ ] Stable [X] Keep from freezing, amines. **Conditions To Avoid -**

Instability:

Incompatibility - Materials To Avoid strong acids, bases, and oxidizing agents.

Avoid:

Hazardous Decomposition Or Carbon monoxide, Carbon dioxide, Nitrogen oxides.

Byproducts:

**Possibility of Hazardous** 

Will occur [ ] Will not occur [X]

Polymerization:

**Conditions To Avoid -**

Will Not occur.

Hazardous Reactions:

11. Toxicological Information

Prolonged exposure may cause dermatitis & skin cracking. Toxicological Information:

Irritation or Corrosion: May cause skin irritation. May cause eye irritation.

Symptoms related to **Toxicological** 

May cause rash on skin, and redness in eyes. May cause coughing by inhalation of a

mist or spray.

Characteristics:

**Chronic Toxicological** 

Effects:

No data available.

12. Ecological Information

General Ecological

Information:

Do not empty into drains. Avoid release to the environment.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

No data available.

Degradability: **Bioaccumulative Potential:** 

not reported, unknown.

**Mobility in Soil:** 

not reported, unknown.

13. Disposal Considerations

Waste Disposal Method:

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge

substance/product into sewage system.

14. Transport Information

LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Not Regulated.

**DOT Hazard Class: UN/NA Number:** 

**Precautionary Label:** Always read Safety Material Data Sheet before use. May cause eye irritation. May

cause skin irritation.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Page: 4

Page: 5 Printed: 10/12/2016 Revision: 10/12/2016

Supersedes Revision: 07/02/2015

MARINE TRANSPORT (IMDG/IMO):

**IMDG/IMO Shipping Name:** Not Regulated.

AIR TRANSPORT (ICAO/IATA):

Not Regulated. ICAO/IATA Shipping Name:

#### 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	Epoxy-Acrylic Copolymer	No	No	No
NA	Styrene-Acrylic Copolymer	No	No	No
29911-28-2	2-Propanol, 1-(2-butoxy-1-methylethoxy)-	No	No	No
84-74-2	Dibutyl phthalate	No	Yes 10 LB	Yes

This material meets the EPA [X] Yes [ ] No Acute (immediate) Health Hazard 'Hazard Categories' defined [ ] Yes [X] No Chronic (delayed) Health Hazard

for SARA Title III Sections [ ] Yes [X] No Fire Hazard

311/312 as indicated: [ ] Yes [X] No Sudden Release of Pressure Hazard

[ ] Yes [X] No Reactive Hazard

**Regulatory Information:** SARA Section 311/312: Acute Health Hazard.

#### 16. Other Information

**Revision Date:** 10/12/2016

**Hazard Rating System:** 

HEALTH **FLAMMABILITY** 0 PHYSICAL 0 PPE Х

HMIS:

Additional Information About CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED

This Product: NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

**Company Policy or** The information contained in this MSDS is taken from sources believed to be accurate as Disclaimer:

of the date hereof; however the Key Resin Company makes no expressed or implied

warranty in respect to the accuracy of the information or the suitability of the

recommendations, and assumes no liabilities to any user thereof.

Licensed to Key Resin Company: MIRS MSDS, (c) A V Systems, Inc.