



## DESCRIPTION

**URECON SL** is a 1/8" – 1/4" seamless, urethane modified, cementitious slurry system that produces a dense, non-porous floor that is chemical and dirt resistant. Ideal for medium to heavy duty traffic areas, **URECON SL** exhibits high impact resistance and excellent thermal shock and chemical resistance. In addition, as a system tolerant to high moisture content in the concrete substrate, **KEY URECON SL** is a solution for many moisture problems. **URECON SL** can be installed with an integral cove base for areas requiring seamless wall to floor coatings. Excellent for rehabbing old floors, the **URECON SL** system provides a strong, long lasting, and attractive surface that resists chemical corrosion, abrasion, and impact.

## KEY ADVANTAGES

- Excellent chemical, wear, and impact resistance
- Unaffected by moisture vapor transmission for on or below grade applications
- May be installed over 5 day old concrete
- Thermal shock resistant
- Hygienic/antimicrobial–will not support bacterial or fungal growth
- Meets USDA requirements for incidental food contact
- Safe for food industry–non-absorbent, non-tainting, washable
- VOC (EPA Method 24) SCAQMD compliant
- Bio-based material, polyol component manufactured using rapidly renewable agricultural content
- Fast cure time
- Low odor application
- Various optional topcoats available–for textured finish refer to **KEY URECON SLT**

## TYPICAL USES

- Concrete floor rehabilitation
- Medium and heavy duty manufacturing
- Packaging areas
- Dry/wet processing areas (for wet processing, verify desired anti-slip performance needed)
- Numerous other uses–consult with Key Resin

## PHYSICAL PROPERTIES

Test Name	Method	Value
Color		Refer to Color Chart
VOC (Volatile Organic Content)	EPA Method 24	Refer to Individual Product Component Data Sheet
Adhesion to Concrete	ASTM D4541	300-400+ psi (Concrete Failure, varies by concrete strength)
Compressive Strength	ASTM C579	7,500 psi
Flexural Strength	ASTM C580	2,600 psi
Hardness, Shore D	ASTM D2240	80-84
Tensile Strength	ASTM C307	1,100 psi
Flammability	ASTM D635	Self Extinguishing
Abrasion Resistance	ASTM D4060, CS17 Wheel, 1000 cycles	32 mg
Impact Resistance	MIL-D-3134J	Withstands 16 ft-lbs without cracking, delamination or chipping
Resistance to Elevated Temperatures	MIL-D-3134J	No slip or flow at required temperature of 158°F

## APPLICATION

### SURFACE PREPARATION

Surface Preparation is the most critical portion of any successful resinous flooring system application. All substrates must be properly prepared as outlined in **Key Resin Technical Bulletin #1**. **KEY URECON SL** may be installed over 5 day old concrete. Be aware that concrete substrates will continue to contract (shrink) during early cure stage possibly causing covered joints to crack--contact Key Resin Technical Service for recommendations. Work must be performed by experienced contractors. The **Key Resin Technical Service Department** is available to answer any questions.

### INSTALLATION

**KEY URECON SL** material components are mixed on site. Refer to the detailed installation instructions document and **Key Resin Technical Service**.

### CLEAN UP

Clean skin with soap and water. Tools and equipment should be cleaned with xylene or lacquer thinner. Consult Safety Data Sheet (SDS) for safety and health precautions.

## MAINTENANCE

After completing the application of **KEY URECON SL**, the installer should provide the owner with maintenance instructions. **KEY URECON SL** is easily cleaned with neutral soaps or detergents. Routine mechanical scrubbing using the appropriate pad is recommended for all surfaces having a slip resistant texture. Refer to **Key Resin Technical Bulletins #3** and **#3-A** for additional recommendations.

## WARRANTY

**Key Resin Company** ("Key") warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed, and applied in accordance with recommendations of Key. If any product fails to meet this warranty, the liability of Key will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Key within (1) one year of delivery of materials. Key may in its discretion refund the price received by Key in lieu of replacing the material. No customer, distributor, or representative of Key is authorized to change or modify the published specifications of this warranty in any way. No one is authorized to make oral warranties on behalf of Key. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. Key reserves the right to inspect the non-conforming material prior to replacement. EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. KEY'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND KEY SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST, EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

## SYSTEM OPTIONS

- Integral Cove Base
- **KEY URECON SC** as outgas preventative primer
- **KEY URECON SC** as topcoat
- **FLOWRESIN FLOWFRESH FC** as topcoat
- **FLOWRESIN FLOWFRESH SR SEALER** as topcoat
- **FLOWRESIN FLOWFRESH FCUV** as topcoat
- Other topcoats may be used over broadcast texture--refer to **KEY URECON SLT**
- May function as moisture mitigation system for other floor coverings--consult with Key Resin

## TECHNICAL SERVICE

**Key Resin Company** provides services and consultations on material selection, specification, troubleshooting, and other information on the proper repair and protection of concrete surfaces. **Key Resin Sales/Technical Representatives** are available to assist. Telephone 888.943.4532 or visit [www.keyresin.com](http://www.keyresin.com).

## AVAILABILITY

**Key Resin** materials are available throughout the United States and a number of other countries. Contact the **Key Resin Representative** in your area for details.

